# D2 CLIP

## D2 Clip Installation configurations on the Style 'E' Drain Cover **HAYWARD 8 INCH ANTI-VORTEX MAIN DRAIN COVER**

www.maindrainclipon.com



### D2 Clip (extra SMALL)

- fits holes 4-3/4" to 5-0" apart

Note: The clip label is hard to read. It is embossed into the clip in the area pictured to the left.



The drain cover pictured to the left is a HAYWARD 8 INCH ANTI-VORTEX MAIN DRAIN COVER.

We refer to drain covers with this design as a Style 'E' Drain Cover.

FIRST REDUCE THE FLOW OF WATER THROUGH THE DRAIN COVER TO A MINIMUM. THIS WILL REDUCE THE SUCTION FORCES BETWEEN THE COVER AND THE POOL CLEANER.

## Style 'E' cover with 1 D2 clip

Install THE CLIP as pictured or clip will be to loose and come off



Centered



**OFF Center** 

Use the "Centered", or "OFF Center" configuration pictured above to keep most "suction cleaners" (Hayward Navigator, Kreepy Krauly, Zodiak, etc.) from getting stuck.

In some cases, due to the shape of the pool bottom in the vicinity of the drain cover, you may need to use a second clip.

Pictured below are some installation patterns when two clips are used on one drain cover (X Pattern, V Pattern, or Off-center PLUS Pattern)



X Pattern



V Pattern



Off-center PLUS

## HOW TO INSTALL THE D2 CLIP (LOW Profile) ON A STYLE "E" DRAIN COVER

#### www.maindrainclipon.com

Place the Installation Tool into the end of your swimming pool utility pole as pictured below.



(1) Insert the **Installation Tool** into the end of your pool utility pole and ensure that the "button" on the tool snaps into the hole on the pole. This will hold the tool in place on the end of your pole.









If you wish, you can use a commonly available "wishbone" (not provided) from your pool brush or basket as pictured.



(2) Insert the **Clip** into the **Installation Tool** as pictured. There is no front or back.



(3) From the side of the pool, position the "hook" of the **Clip** into the "slotted" hole closest to you.



(4) Stretch the Clip across the drain cover and place the opposite end "hook" into the most distant "round" hole on the top of the drain cover.
This is a pushing motion.



Shown: the most distant "round" hole on the top of the drain cover on the opposite side of the drain cover.



(5) After both "hooks" are in place on the drain cover, the **Clip** will be "pinching" the drain cover and not the Installation Tool.

(6) Now, gently wiggle the pole while moving it to the side to remove the tool from the clip.



(7) Use the utility pole as pictured above to push on the end of the clip and securely "seat" the hook into the holes.